



NEOCOLORI

Colori dell'Italia

Cera Garde

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Cera Garde is transparent water based paste wax for the protection of specific synthetic and Venetian plaster with lime. Application produces a higher gloss polished stucco which provide the wash ability and water resistance also it gives a greater uniformity of final color. It is non-toxic VOC (<80) L/A 200g/l (2010).

Thinner: Water

Drying time: touch dry 2 hours, 6 to 8 h between coats


Yield: 15m² per 1 lit

Flammability: Not flammable

S46 If swallowed, immediately contact a doctor and show him the packaging and labeling

Date: Marked on the packaging

Application: Surface must be clean and dry. Stucco must be finished minimum 15 days before we start with application of Cera Garde. Apply directly on the stucco finish and polished it with a stainless steel spatula, with a very low thickness. Leave to absorb and dry at least 2 hours. Then proceed to final leveling always with a stainless steel spatula.



COMPOSITION

Special emulsion water based wax, non-toxic additives.

METHOD OF APPLICATION

Apply directly on the stucco finish with stainless steel spatula and polished with a stainless steel spatula, with a very low thickness leave to absorb and dry at least 2 hours proceed to final leveling always with a stainless steel spatula.

TECHNICAL DATA

Specific weight: 0,962 kg/lit +/- 1%

Viscosity: Thixotropic paste

Drying: touch dry after 2 hours at 20°, completely dry 24 hours at 20°

Application temperature: between 5°C and 30°C

Yield: 15 m²/lit

Color: transparent

Package: in buckets of 1 lit and 4 lit polyethylene containers

Package: Cera Garde is available in 1 lit and 4 lit or bigger package for projects

Application: apply with a special stainless-steel spatula

Preservation: 24 months in the intact package, away from temperature changes

ITEM OF SPECIFICATIONS

Protection of wall surfaces for **Stucco Veneziano** and **Vulcano Travertino**.